

jura[®]



E6 (EA/SA/INTA/EB/SB)
Instructions for Use

Your E6

Control elements	4
Important information	6
Proper use	6
For your safety	6
1 Preparing and using for the first time	10
Setting up the machine	10
Filling the bean container	10
Determining the water hardness	10
First-time use	11
Connecting milk	12
Connect accessory (with wireless connection)	13
2 Preparation	14
Espresso and coffee	14
Two espressi and two coffees	14
Cappuccino and macchiato	15
Caffè Barista and lungo Barista	15
Espresso doppio	16
Milk foam	16
Hot water	17
Permanently setting the amount of water for the cup size	17
Adjusting the grinder	18
3 Daily operation	19
Filling the water tank	19
Switching on the machine	19
Daily maintenance	19
Regular maintenance	20
Switching off the machine	20
4 Permanent settings in programming mode	22
Adjusting the product settings	22
Automatic switch-off	24
Setting the water hardness	24
Language	25
Unit for amount of water	25
5 Maintenance	26
Rinsing the machine	26
Rinsing the fine foam frother	26
Cleaning the fine foam frother	27
Dismantling and rinsing the fine foam frother	28
Inserting/changing the filter	28

Cleaning the machine	29
Descaling the machine	30
Descaling the water tank.....	32
Cleaning the bean container.....	33
6 Display messages	34
7 Troubleshooting	35
8 Transport and environmentally friendly disposal	37
Transport / Emptying the system.....	37
Disposal.....	37
9 Technical data	38
10 Index	39
11 JURA contact details / Legal information	44

Scope of validity



These instructions for use apply to the following models:

- E6
- E60

In the interests of clarity, however, the instructions for use only refer to the 'E6' model.


Symbol description


Warnings

 WARNING	Always take note of any information marked with the words CAUTION or WARNING and a warning sign. The signal word WARNING draws your attention to potential serious injury, and the signal word CAUTION to potential minor injury.
 CAUTION	

CAUTION	CAUTION draws your attention to potential damage to the machine.
----------------	---

Symbols used


	Prompt to take action. This symbol means that you are being prompted to perform some action.
---	---

	Information and tips to make it even easier to use your E6.
---	--

	Display
---	----------------


Control elements



- | | | | |
|---|--|----|---|
| 1 | Cover of filler funnel for cleaning tablet | 9 | Cover for grinder adjustment switch |
| 2 | Filler funnel for cleaning tablet | 10 | Grinder adjustment switch |
| 3 | Bean container with aroma preservation cover | 11 | On/Off button  |
| 4 | Water tank cover | 12 | Fine foam frother |
| 5 | Water tank | 13 | Height-adjustable coffee spout |
| 6 | Mains cable (back of the machine) | 14 | Cup grille |
| 7 | Coffee grounds container | | |
| 8 | Drip tray | | |



- 1 Display
- 2 Multi-function buttons (button function depends on what is shown in the display)
- 3 Switch for hot water and steam preparation



Service socket for optional JURA Smart Connect

Important information

Proper use

The machine is designed and intended for private domestic use. It should only be used for coffee preparation and to heat milk and water. Use for any other purpose will be deemed improper. JURA Elektroapparate AG cannot accept any responsibility for the consequences of improper use.

Before using the machine read these instructions for use thoroughly and completely and comply with the instructions they contain. A warranty service is not applicable for damage or defects caused by non-compliance with the instructions for use. Keep these instructions for use close to the machine and pass them on to the next user.


For your safety

Please carefully read and observe the important safety information set out below.



To avoid danger of potentially fatal electric shock:

- Never use a machine which is damaged or has a defective mains cable.
- In the event of signs of damage, for example if there is a smell of burning, unplug the machine immediately from the power supply and contact JURA service.
- For models with a permanently connected mains cable: If the mains cable of this machine is damaged, it must be repaired either directly by JURA or by an authorised JURA service centre.
- For machines with a plug-in mains cable: If the mains cable of this machine is damaged it must be replaced with a special mains cable, which is available directly from JURA or from authorised JURA service centres.
- Make sure that the E6 and the mains cable are not located close to hot surfaces.



- Be careful to ensure that the mains cable is not trapped and does not rub against sharp edges.
- Never open and repair the machine yourself. Do not modify the machine in any way that is not described in these instructions for use. The machine contains live parts. If opened, there is a danger of potentially fatal injury. Repairs may only be carried out by authorised JURA service centres, using original spare parts and accessories.
- To completely and safely disconnect the machine from the power supply, first switch off the E6 using the On/Off button . Only then should you remove the mains plug from the power socket.

There is a risk of scalds or burns on the spouts and fine foam frother:

- Place the machine out of the reach of children.
- Do not touch any hot parts. Use the handles provided.
- Be careful to ensure that the fine foam frother is correctly installed and clean. If incorrectly fitted or if it becomes blocked, the fine foam frother or its parts might come off.
- Your E6 can be remotely operated using mobile devices. When preparing a product or initiating a maintenance programme, make sure that other people are not put at risk – for example, through contact with the spouts.

A defective machine is not safe and could cause injury or fire. To avoid damage and any associated risk of injury or fire:

- Never allow the mains cable to loosely hang down. The mains cable could pose a tripping hazard or become damaged.

- Protect the E6 from environmental influences such as rain, frost and direct sunlight.
- Before cleaning, switch the E6 off with the On/Off button . Always wipe the E6 with a damp cloth rather than a wet one, and protect it from prolonged exposure to water splash.
- Do not immerse the E6, mains cable or connections in water.
- Do not put the E6 or any individual parts in the dishwasher.
- Do not use alkaline cleaning agents; only use a soft cloth and mild cleaning agents.
- Only connect the machine to the mains voltage in accordance with the information on the rating plate. The rating plate is located on the underside of your E6. Further technical data is provided in these instructions for use (see Chapter 9 'Technical data').
- Connect the E6 directly to a domestic power socket. Using multi-socket adapters or extension cords may cause overheating.
- Please only use original JURA maintenance products. Use of products that are not explicitly recommended by JURA could damage the machine.
- Do not use any coffee beans treated with additives or caramelised coffee beans.
- Only fill the water tank with fresh, cold water.
- Switch the machine off with the On/Off button  if you are going to be absent for a longer period of time and remove the mains plug from the power socket.
- Children may not clean or service the machine unless supervised by a responsible person.
- Do not allow children to play with the machine.

- Keep children under the age of 8 away from the machine, or supervise them constantly.
- Children aged 8 and over may only operate the machine without supervision if they have been instructed in how to use it safely. Children must be able to recognise and understand the potential dangers arising from incorrect use.

People, including children, who

- do not have the physical, sensory or mental capabilities to use the machine safely or
- are inexperienced or lack knowledge in how to use the machine safely


must be supervised by a responsible person when using it, or must be instructed in how to use it correctly.

Safety when handling the CLARIS Smart filter cartridge:

- Filter cartridges should be kept out of the reach of children.
- Store filter cartridges in a dry place in the sealed packaging.
- Protect cartridges from heat and direct sunlight.
- Do not use damaged filter cartridges.
- Do not open filter cartridges.
- The CLARIS Smart filter cartridge communicates with your E6 via RFID technology (frequency band 13.56 MHz). This wireless connection is only used for a maximum of 3 sec. during preparation. In this case, the maximum transmission power is below 1 mW.

1 Preparing and using for the first time

Setting up the machine



When setting up your E6, please note the following:

- Place the E6 on a horizontal surface that is not sensitive to water.
- Choose a spot for your E6 which protects the machine against overheating. Ensure that the ventilation slots are not covered.

Filling the bean container

CAUTION


Coffee beans which have been treated with additives (e.g. sugar), ground coffee or freeze-dried coffee will damage the grinder.

- ▶ Only use roasted, untreated coffee beans to fill the bean container.
-
- ▶ Remove the aroma preservation cover.
 - ▶ Remove any dirt or foreign objects from inside the bean container.
 - ▶ Fill the bean container with coffee beans and close the aroma preservation cover.

Determining the water hardness

When you use the machine for the first time, you must set the water hardness. If you do not know the hardness of your water, you can find this out first. Use the Aquadur® test strips supplied with the machine.

- ▶ Hold the test strip briefly (for 1 second) under flowing water. Shake off the water.
- ▶ Wait for about 1 minute.



- ▶ You will then be able to read the degree of water hardness from the discolouration of the Aquadur® test strip and the description on the packaging.

First-time use

⚠ WARNING

If the machine is operated with a defective mains cable, there is a danger of potentially fatal electric shock.


- ▶ Never use a machine which is damaged or has a defective mains cable.

⚠ CAUTION

Milk, sparkling mineral water or other liquids can damage the water tank or the machine.

- ▶ Only fill the water tank with fresh, cold water.

Precondition: The bean container has been filled.

- ▶ Insert the mains plug into a power socket.
- ▶ Press the On/Off button  to switch the E6 on.

‘Sprachauswahl’

i To display more languages, press the ‘>’ button.

- ▶ Press the button that corresponds to the language you want, e.g. ‘English’.

‘Saved’ appears briefly on the display.

‘Water hardness’

i If you do not know the hardness of your water, you must find this out first (see Chapter 1 ‘Preparing and using for the first time – Determining the water hardness’).


- ▶ Press the ‘<’ or ‘>’ button to change the setting for the water hardness.

- ▶ Press the ‘Save’ button.

‘Saved’ appears briefly on the display.

‘Filter operation’

1 Preparing and using for the first time




- ▶ Place a receptacle under the fine foam frother and under the coffee spout.
- ▶ Remove the water tank and rinse it with cold water.
- ▶ Fit the filter cartridge extension supplied on top of the CLARIS Smart filter cartridge.

- ▶ Insert the filter cartridge with its extension into the water tank.
- ▶ Turn the filter cartridge clockwise until it audibly clicks into place.
- ▶ Fill the water tank with fresh, cold water and reinsert the tank.


i The machine automatically detects that you have just inserted the filter cartridge.

‘Saved’ appears briefly on the display.

‘Open switch’

- ▶ Turn the switch to the  position.
‘Filter is being rinsed’, water flows out of the fine foam frother.

Rinsing of the filter stops automatically. ‘Close switch’ appears on the display.

- ▶ Turn the switch to the  position.

‘System is filling’

‘Empty drip tray’

- ▶ Empty the drip tray and put it back into the machine.


‘Machine is rinsing’

The start screen is displayed. Your E6 is ready for use.


The CLARIS Smart filter cartridge communicates with your E6 via RFID technology (frequency band 13.56 MHz). This wireless connection is only used for a maximum of 3 sec. during preparation. In this case, the maximum transmission power is below 1 mW.

Connecting milk

Your E6 creates fine, creamy, feather-light milk foam with a perfect consistency. The most important requirement for frothing milk is a milk temperature of 4–8 °C. We would therefore recommend using a milk cooler or a milk container.



- ▶ Remove the protective cover from the fine foam frother.



- ▶ Connect the milk pipe to the fine foam frother.
- ▶ Connect the other end of the milk pipe to a milk container or a milk cooler.

Connect accessory (with wireless connection)

You have the option of connecting your E6 wirelessly to a compatible accessory (e.g. the Cool Control milk cooler). To do this, the receiver of the Cool Control or the JURA Smart Connect must be plugged into the service socket.

A frequency band of 2.4 GHz is used for this wireless connection. In this case, the maximum transmission power is below 1 mW.

- i** The Smart Connect can be protected against unauthorised access using a PIN. Activate the PIN function via J.O.E.[®] – your JURA app. You will find more information at jura.com/smartconnect.
- i** Please note that you can only connect either the accessory or J.O.E.[®] to the coffee machine via Smart Connect and not both at the same time.

Precondition: The start screen is displayed.

- ▶ Position the accessory near the coffee machine (a maximum of 0.5 m away).
- ▶ Switch on the accessory and the coffee machine.
- ▶ Press the reset button of the Smart Connect (e.g. with a paper clip).
- ▶ Then (within 30 sec.) press and hold the reset button of the accessory until the LED lights up to indicate the successful connection.

2 Preparation

Basic information about preparing drinks:

- The display shows four products you can prepare. Press the '>' button to display more products.
- During the grinding operation you can select the coffee strength of **single products** by pressing the '<' and '>' buttons.
- During preparation you can change the preset **amounts** (e.g. water and amount of milk foam) by pressing the '<' and '>' buttons.
- You can make **permanent settings** for all products in programming mode (see Chapter 4 'Permanent settings in programming mode – Adjusting the product settings').
- You can stop preparation at any time. To do this, press the 'Cancel' button.

Coffee tastes best served hot. A cold porcelain cup cools the beverage – and impairs the taste. We therefore recommend prewarming the cups. The full coffee aroma can develop only in prewarmed cups. You can purchase a JURA cup warmer from your specialised dealer.

Espresso and coffee



Example: Proceed as follows to prepare one coffee.

Precondition: The start screen is displayed.

- ▶ Place a cup under the coffee spout.
- ▶ Press the 'Coffee' button.

The preset amount of water for coffee flows into the cup.

Two espressi and two coffees

To prepare **two** speciality coffees, press the appropriate preparation button twice (within approximately 1 second).

Example: Proceed as follows to prepare two espressi.

Precondition: The start screen is displayed.



- ▶ Place two cups under the coffee spout.
- ▶ Press the 'Espresso' button **twice (within 1 second)**. '2 x Espresso', the preset amount of water flows into the cups.

Cappuccino and macchiato



Example: Proceed as follows to prepare one cappuccino.


Precondition: The start screen is displayed. Milk is connected to the fine foam frother.

- ▶ Place a cup under the coffee spout and the fine foam frother.


i When preparing a macchiato, depending on the size of the cup, the cup may need to be moved to under the coffee spout after the milk foam has been prepared.

- ▶ Press the 'Cappuccino' button.

As soon as the machine has heated up, 'Open switch' appears.

- ▶ Turn the switch to the  position.
The milk foam is prepared.

'Close switch'

- ▶ Turn the switch to the  position.

The preset amount of water for espresso flows into the cup.

To ensure that the fine foam frother always works properly, you must clean it **daily** when you have been preparing milk (see Chapter 5 'Maintenance – Cleaning the fine foam frother').

Caffè Barista and lungo Barista

For the 'caffè Barista' and 'lungo Barista', blend the coffee with hot water. This results in a full-bodied speciality coffee which is particularly easy to digest. You can change the amount of this additional water (see Chapter 4 'Permanent settings in programming mode – Adjusting the product settings').

Example: Proceed as follows to prepare a 'caffè Barista'.

Precondition: The start screen is displayed.

2 Preparation



- ▶ Place a cup under the coffee spout and the fine foam frother.
- ▶ Press the 'Caffè Barista' button.
The preset amount of water for coffee flows into the cup.
'Open switch'
- ▶ Turn the switch to the ☰ position.
Hot water flows out of the fine foam frother.
'Close switch'
- ▶ Turn the switch to the ① position.

Espresso doppio

'Doppio' is Italian for 'double'. When you select Espresso doppio, two espressos are prepared one after the other. The result is an extra full-bodied and aromatic speciality coffee.

Milk foam



Precondition: The start screen is displayed. Milk is connected to the fine foam frother.

- ▶ Place a cup under the fine foam frother.
- ▶ Press the 'Milk foam' button
As soon as the machine has heated up, 'Open switch' appears.
- ▶ Turn the switch to the ☰ position.
The milk foam is prepared.
'Close switch'
- ▶ Turn the switch to the ① position.

To ensure that the fine foam frother always works properly, you must clean it **daily** when you have been preparing milk (see Chapter 5 'Maintenance – Cleaning the fine foam frother').

Hot water

⚠ CAUTION

There is a danger of scalding from hot water splashes.

- ▶ Avoid direct contact with the skin.



Precondition: The start screen is displayed.

- ▶ Place a cup under the fine foam frother.
- ▶ Turn the switch to the ☰ position.
The preset amount of water flows into the cup.
'Close switch'
- ▶ Turn the switch to the Ⓛ position.

Permanently setting the amount of water for the cup size

It is easy to permanently adjust the amount of water for all **single products** to the cup size. Adjust the amount once as shown in the following example. Every time you prepare a drink in the future, this amount will be dispensed.

Example: Proceed as follows to **permanently** set the amount of water for one coffee.

Precondition: The start screen is displayed.

- ▶ Place a cup under the coffee spout.
- ▶ Press and **hold** the **'Coffee'** button until **'Enough coffee? Press button'** appears.
- ▶ Release the **'Coffee'** button.
Preparation starts and the coffee flows into the cup.
- ▶ Press any button except **'Cancel'** as soon as there is sufficient coffee in the cup.
Preparation stops. **'Saved'** appears briefly on the display.



- i** You can alter this setting at any time by repeating the above procedure.
- i** You can also permanently set the amounts for all single products in programming mode (see Chapter 4 'Permanent settings in programming mode – Adjusting the product settings').

Adjusting the grinder

You can adjust the grinder to suit the degree of roast of your coffee.

CAUTION

If you adjust the consistency of grind when the grinder is not operating, the grinder adjustment switch could be damaged.

- ▶ Only adjust the consistency of grind when the grinder is running.
-

The consistency of grind is correct if the coffee flows regularly from the coffee spout. In addition a fine, thick crema forms.

Example: Proceed as follows to change the consistency of grind during the preparation of an espresso.

Precondition: The start screen is displayed.

- ▶ Place a cup under the coffee spout.
- ▶ Open the cover of the grinder adjustment switch.
- ▶ Press the 'Espresso' button to start preparation.
- ▶ Turn the grinder adjustment switch to the desired position **while** the grinder is running.

The preset amount of water flows into the cup. Preparation stops automatically.

- ▶ Close the cover of the grinder adjustment switch.



3 Daily operation

Filling the water tank

Daily maintenance of the machine and hygiene when handling milk, coffee and water are key to a perfect coffee result in the cup every time. You should therefore change the water **daily**.


CAUTION

Milk, sparkling mineral water or other liquids can damage the water tank or the machine.

-
- ▶ Only fill the water tank with fresh, cold water.
-
- ▶ Open the water tank cover.
 - ▶ Remove the water tank and rinse it with cold water.
 - ▶ Fill the water tank with fresh, cold water and reinsert the tank.
 - ▶ Close the water tank cover.

Switching on the machine



- ▶ Place a receptacle under the coffee spout.
- ▶ Press the On/Off button  to switch the E6 on.
‘Machine is rinsing’, rinsing stops automatically. The start screen is displayed.

Daily maintenance



To ensure that you get many years of reliable service out of your E6 and to guarantee the optimum coffee quality, the machine requires daily maintenance.

- ▶ Pull out the drip tray.
 - ▶ Empty the coffee grounds container and the drip tray. Rinse them both with warm water.
- i** Always empty the coffee grounds container when the machine is **switched on**. This is the only way of resetting the coffee grounds counter.
- ▶ Refit the coffee grounds container and the drip tray.

- ▶ Clean the fine foam frother (see Chapter 5 ‘Maintenance – Cleaning the fine foam frother’).
- ▶ Remove the milk pipe and rinse it thoroughly under running water.
- ▶ Dismantle and rinse the fine foam frother (see Chapter 5 ‘Maintenance – Dismantling and rinsing the fine foam frother’).
- ▶ Rinse the water tank with clean water.
- ▶ Wipe the surface of the machine with a clean, soft, damp cloth (e.g. microfibre cloth).

You will find more information about caring for your E6 in programming mode (page ‘2/4’) under ‘Information’.

Regular maintenance


Carry out the following maintenance actions **regularly** or as **required**:

- In the interests of hygiene, we recommend changing the milk pipe and interchangeable milk spout on a regular basis (approximately every 3 months). Replacements are available from specialised dealers. Your E6 is equipped with the **HP1** milk system.
- Clean the inside of the water tank, e.g. with a brush. Further information about the water tank is provided in these instructions for use (see Chapter 5 ‘Maintenance – Descaling the water tank’).
- Traces of milk and coffee may stick to the top and bottom of the cup grille. If this happens, clean the cup grille.

Switching off the machine




When the E6 is switched off, the system is automatically rinsed if a speciality coffee has been prepared.

- ▶ Place a receptacle under the fine foam frother and under the coffee spout.
- ▶ Press the On/Off button .

- i** If milk has been prepared, you will be prompted to clean the milk system (‘**Clean the milk system**’). After 10 seconds the switch-off process continues automatically.


‘Machine is rinsing’

If milk has been prepared but you have not started milk system cleaning, you will first need to rinse the milk system ('Rinse the milk system' / 'Open switch').

- ▶ Turn the switch to the  position.

'Milk system is being rinsed'

'Close switch'

- ▶ Turn the switch to the  position.

Your E6 is switched off.

4 Permanent settings in programming mode

Press the 'P' button to enter programming mode. You can navigate through the programme items and permanently save the required settings using the multi-function buttons. The following settings can be made:

Programme item	Sub-item	Explanation
'1/4'	'Clean', 'Descale', 'Clean the milk system', 'Filter' (only if filter is fitted)	▶ Start the required maintenance programme here.
'2/4'	'Rinse the coffee system', 'Rinse the milk system', 'Information'	▶ Here you can start the desired maintenance programme or find out what maintenance actions are required.
'3/4'	'Expert mode'	▶ Select your settings for speciality coffees and hot water.
'4/4'	'Choose language'	▶ Select your language.
	'Units'	▶ Select the unit for the amount of water.
	'Switch off after'	▶ Set the time after which the E6 should switch off automatically.
	'Water hardness'	▶ You can set the water hardness of the water used.

Adjusting the product settings

In the programme item 'Expert mode' you can make individual settings for all speciality coffees and hot water. The following permanent settings can be made:

Product	Coffee strength	Amount	Temperature
'Espresso'	8 levels	Water: 15 ml – 80 ml	normal, high
'Coffee'	8 levels	Water: 25 ml – 240 ml	normal, high
'2 x Espresso', '2 x Coffee'	–	Water: the amount set for the single product is doubled.	as for single product
'Caffè Barista', 'Lungo Barista'	8 levels	Water: 25 ml – 240 ml Bypass water: 0 ml – 240 ml	

Product	Coffee strength	Amount	Temperature
'Espresso doppio' (2 brewing operations)	8 levels	Water: 30 ml – 160 ml	normal, high
'Cappuccino'	8 levels	Water: 25 ml – 240 ml Milk foam: 3 sec. – 120 sec.	normal, high
'Macchiato'	8 levels	Water: 15 ml – 80 ml Milk foam: 3 sec. – 120 sec.	normal, high
'Milk foam'	–	Milk foam: 3 sec. – 120 sec.	–
'Hot water'	–	Water: 25 ml – 450 ml	low, normal, high

Permanent settings in programming mode always follow the same model.

Example: Proceed as follows to change the coffee strength for one coffee.

Precondition: The start screen is displayed.

- ▶ Press the '**P**' button.
- ▶ Press the '>' button several times until page '3/4' is displayed.
- ▶ Press the '**Expert mode**' button.

i Next select the button of the product for which you would like to make settings. No product is prepared at this point.

i To display more products, press the '>' button.

- ▶ Press the '**Coffee**' button.
- ▶ Press the '**Coffee strength**' button.
- ▶ Press the '<' or '>' button to change the setting for the coffee strength.
- ▶ Press the '**Save**' button.
'Saved' appears briefly on the display.
- ▶ Press the '**L**' button for **around 2 seconds** to exit programming mode.

Automatic switch-off

By instructing your E6 to automatically switch itself off, you can cut down your energy consumption. If this function is activated, your E6 switches off automatically after the preset time following the last action on the machine.

You can set the automatic switch-off to 15 minutes, 30 minutes or 1–9 hours.

Precondition: The start screen is displayed.

- ▶ Press the 'P:⚡' button.
- ▶ Press the '>' button several times until page '4/4' is displayed.
- ▶ Press the 'Switch off after' button.
- ▶ Press the '<' or '>' button to change the switch-off time.
- ▶ Press the 'Save' button.
'Saved' appears briefly on the display.
- ▶ Press the 'L' button to exit programming mode.

Setting the water hardness

The harder the water is, the more frequently the E6 needs to be descaled. It is therefore important to set the water hardness accurately.

The water hardness was set when the machine was first used. You can change this setting at any time.

The water hardness can be adjusted on a continuous scale between 1 °dH and 30 °dH.

Precondition: The start screen is displayed.

- ▶ Press the 'P:⚡' button.
- ▶ Press the '>' button several times until page '4/4' is displayed.
- ▶ Press the 'Water hardness' button.
- ▶ Press the '<' or '>' button to change the setting for the water hardness.
- ▶ Press the 'Save' button.
'Saved' appears briefly on the display.
- ▶ Press the 'L' button to exit programming mode.

Language

In this programme item you can set the language used by your E6.

Example: Proceed as follows to change the language from 'English' to 'Deutsch'.

Precondition: The start screen is displayed.

- ▶ Press the 'P:.' button.
- ▶ Press the '>' button several times until page '4/4' is displayed.
- ▶ Press the 'Choose language' button.

i To display more languages, press the '>' button.

- ▶ Press the button that corresponds to the language you want, e.g. 'Deutsch'.
'Gespeichert' appears briefly on the display.
- ▶ Press the 'L' button to exit programming mode.

Unit for amount of water

In the programme item 'Units' you can set the unit used for the amount of water.

Example: Proceed as follows to change the unit for the amount of water from 'ml' to 'oz'.

Precondition: The start screen is displayed.

- ▶ Press the 'P:.' button.
- ▶ Press the '>' button several times until page '4/4' is displayed.
- ▶ Press the 'Units' button.
- ▶ Press the 'oz' button.
- ▶ Press the 'Save' button.
'Saved' appears briefly on the display.
- ▶ Press the 'L' button to exit programming mode.

5 Maintenance

Basic information about maintenance:

- Press the 'P:⚠️' button to view a list of the maintenance programmes. When the bar is completely filled with red, your E6 will prompt you to perform the appropriate maintenance programme.
- Carry out each maintenance programme when you are prompted to do so.
- In the interests of hygiene, you should clean the fine foam frother **daily** when you have been preparing milk.

Rinsing the machine

You can start coffee system rinsing manually at any time.

Precondition: The start screen is displayed.



- ▶ Place a receptacle under the coffee spout.
- ▶ Press the 'P:⚠️' button.
- ▶ Press the '>' button.
- ▶ Press the 'Rinse the coffee system' button to start the rinse operation.
The operation stops automatically.



Rinsing the fine foam frother

After each milk preparation, the E6 prompts you to perform a milk system rinse.

Precondition: 'Rinse the milk system' is displayed.

- ▶ Place a receptacle under the fine foam frother.
- ▶ Press the 'P:⚠️' button.
'Open switch'
- ▶ Turn the switch to the  position.
The fine foam frother is rinsed.
'Close switch'
- ▶ Turn the switch to the  position.



Cleaning the fine foam frother

To ensure that the fine foam frother always works properly, you must clean it **daily** when you have been preparing milk

CAUTION

If the wrong cleaning agent is used, the machine could be damaged and/or traces could be left behind in the water.

- ▶ Use only original JURA maintenance products.

i JURA milk system cleaner is available from specialised dealers.

Precondition: The start screen is displayed.

- ▶ Press the 'P:☼' button.
 - ▶ Press the 'Clean the milk system' button.
 - ▶ Press the 'Start' button.
 - ▶ Press the 'Next' button.
- 'Milk system cleaner'
- ▶ Remove the milk pipe from the milk container or milk cooler.
 - ▶ Pour 250 ml of warm water into a receptacle and add 1 dosing unit of milk system cleaner.
 - ▶ Immerse the milk pipe in the receptacle.




- ▶ Place a receptacle under the fine foam frother.
 - ▶ Press the 'Next' button.
- As soon as the machine has heated up, 'Open switch' appears.
- ▶ Turn the switch to the ☼ position.
- The fine foam frother and the milk pipe are cleaned.
- 'Close switch'
- ▶ Turn the switch to the Ⓢ position.
- 'Fresh water'
- ▶ Rinse the receptacle thoroughly, fill it with 250 ml of fresh water and immerse the milk pipe in the water.
 - ▶ Empty the other receptacle and place it under the fine foam frother once more.
 - ▶ Press the 'Next' button.
- 'Open switch'

- ▶ Turn the switch to the ☺ position.
The fine foam frother and the milk pipe are rinsed with fresh water.
'Close switch'
- ▶ Turn the switch to the ⓪ position.

Dismantling and rinsing the fine foam frother

To make sure the fine foam frother works properly, and in the interests of hygiene, it must be dismantled and rinsed **daily** if you have been preparing milk.



- ▶ Remove the milk pipe and rinse it thoroughly under running water.
- ▶ Remove the fine foam frother.
- ▶ Dismantle the fine foam frother into its individual parts.
- ▶ Rinse all the parts under running water. If there are severely dried-on milk residues, firstly immerse the individual parts in a solution of 250 ml warm water and 1 dosing unit of milk system cleaner. Then rinse the parts thoroughly.
- ▶ Re-assemble the fine foam frother.

- i** Ensure that all individual parts are correctly and firmly connected to ensure optimum operation.
- ▶ Re-fit the fine foam frother on the milk system.


Inserting/changing the filter

Your E6 no longer has to be descaled if you are using the CLARIS Smart filter cartridge.

- i** Once the filter cartridge stops working (depending on the water hardness setting), the E6 will prompt you to change the filter.
- i** CLARIS Smart filter cartridges are available from specialised dealers.



Precondition: The start screen is displayed. The filter symbol ☺ lights up red (if you are already using a filter and it is depleted).

- ▶ Remove and empty the water tank.
- ▶ Turn the filter cartridge anticlockwise and remove it along with the extension from the water tank.
- ▶ Fit the filter cartridge extension on top of a **new** CLARIS Smart filter cartridge.




- ▶ Insert the filter cartridge with its extension into the water tank.
- ▶ Turn the filter cartridge clockwise until it audibly clicks into place.
- ▶ Fill the water tank with fresh, cold water and reinsert the tank.
The machine automatically detects that you have just inserted/changed the filter cartridge.

‘Open switch’

- ▶ Turn the switch to the  position.
‘Filter is being rinsed’
- ▶ Turn the switch to the  position.

‘Close switch’

- ▶ Turn the switch to the  position.




Cleaning the machine

After 180 preparations or 80 switch-on rinses, the E6 will prompt you to clean it.

CAUTION

If the wrong cleaning agent is used, the machine could be damaged and/or traces could be left behind in the water.

- ▶ Use only original JURA maintenance products.

-  The cleaning programme lasts approximately 20 minutes.
-  Do not interrupt the cleaning programme. The quality of cleaning will be impaired if you do so.
-  JURA cleaning tablets are available from specialised dealers.

Precondition: ‘Clean machine’ is displayed.

- ▶ Press the ‘P:⚙️’ button.
‘Clean’
- ▶ Press the ‘Start’ button.
- ▶ Press the ‘Next’ button.
‘Empty coffee grounds container’
- ▶ Empty the drip tray and coffee grounds container and put them back into the machine.
‘Clean’

5 Maintenance



- ▶ Place a receptacle under the coffee spout.
- ▶ Press the 'Next' button.
'Machine is being cleaned', water flows out of the coffee spout.
The operation is interrupted, 'Add cleaning tablet'.
- ▶ Open the cover of the filler funnel for the cleaning tablet.
- ▶ Insert a JURA cleaning tablet into the filler funnel.
- ▶ Close the cover of the filler funnel.
- ▶ Press the 'Next' button.
'Machine is being cleaned', water flows out of the coffee spout several times.
The operation stops automatically.
'Empty coffee grounds container'
- ▶ Empty the drip tray and coffee grounds container and put them back into the machine.

Descaling the machine

The E6 builds up deposits of limescale over time and automatically prompts you to descale it when necessary. The degree of calcification depends on the hardness of your water.

i If you are using a CLARIS Smart filter cartridge, you will not be prompted to descale.

⚠ CAUTION If the descaling agent comes into contact with the skin or eyes, this can cause irritation.

- ▶ Avoid contact with the skin or eyes.
- ▶ Rinse off the descaling agent with clean water. Should you get any descaling agent in your eye, see a doctor.

CAUTION If the wrong descaling agent is used, the machine could be damaged and/or traces could be left behind in the water.

- ▶ Use only original JURA maintenance products.

CAUTION If the descaling operation is interrupted, there may be damage to the machine.

- ▶ Allow the descaling programme to run to the end.
-


CAUTION If the descaling agent comes into contact with sensitive surfaces (e.g. marble), damage cannot be ruled out.

- ▶ Clean up any splashes immediately.

- i** The descaling programme lasts approximately 40 minutes.
- i** JURA descaling tablets are available from specialised dealers.



Precondition: 'Decalcify machine' is displayed.

- ▶ Press the 'P:⌘:' button.
'Descale'
- ▶ Press the 'Start' button.
- ▶ Press the 'Next' button.
'Empty drip tray'
- ▶ Empty the drip tray and coffee grounds container and put them back into the machine.
'Agent in tank'
- ▶ Remove and empty the water tank.
- ▶ Completely dissolve 3 JURA descaling tablets in a receptacle holding 500 ml of water. This may take several minutes.
- ▶ Pour the solution into the **empty** water tank and insert it into the machine.
'Open switch'



- ▶ Place a receptacle under the fine foam frother.
- ▶ Turn the switch to the ☰ position.
'Machine is being descaled' appears and water flows out of the fine foam frother repeatedly.
The operation is interrupted, 'Close switch'.
- ▶ Turn the switch to the Ⓢ position.
'Machine is being descaled', the descaling operation is continued.
The operation is interrupted, 'Empty drip tray'.
- ▶ Empty the drip tray and coffee grounds container and put them back into the machine.
'Rinse the water tank' / 'Fill water tank'



- ▶ Empty the receptacle and place it under the fine foam frother and the coffee spout.
- ▶ Remove the water tank and rinse it thoroughly.
- ▶ Fill the water tank with fresh, cold water and reinsert the tank.
'Open switch'
- ▶ Turn the switch to the  position.
'Machine is being descaled', the descaling operation is continued.
The operation is interrupted, **'Close switch'**.
- ▶ Turn the switch to the  position.
The descaling operation is continued. Water flows out of the coffee spout.
The operation is interrupted **'Empty drip tray'**
- ▶ Empty the drip tray and coffee grounds container and put them back into the machine.

i If the descaling operation stops unexpectedly, rinse the water tank thoroughly.

Descaling the water tank


Limescale deposits may form in the water tank. To ensure correct function of the machine, descale the water tank from time to time.

- ▶ Remove the water tank.
- ▶ If you use a CLARIS Smart filter cartridge, remove this.
- ▶ Completely fill the water tank and dissolve 3 JURA descaling tablets in it.
- ▶ Leave the water tank with the descaling solution for several hours (e.g. overnight).
- ▶ Empty the water tank and rinse it thoroughly.
- ▶ If you use a CLARIS Smart filter cartridge, insert this again.
- ▶ Fill the water tank with fresh, cold water and reinsert the tank.

Cleaning the bean container

Coffee beans may be covered with a slight oil film which remains on the walls of the bean container. These traces may negatively affect the coffee result. For this reason clean the bean container from time to time.

Precondition: 'Fill bean container' is displayed.

- ▶ Switch the machine off with the On/Off button .
- ▶ Remove the aroma preservation cover.
- ▶ Clean the bean container with a soft, dry cloth.
- ▶ Fill the bean container with coffee beans and close the aroma preservation cover.


6 Display messages

Message	Cause/Result	Action
'Fill water tank'	The water tank is empty. You cannot prepare any products.	▶ Fill the water tank (see Chapter 3 'Daily operation – Filling the water tank').
'Empty coffee grounds container'	The coffee grounds container is full. You cannot prepare any products.	▶ Empty the coffee grounds container and the drip tray (see Chapter 3 'Daily operation – Daily maintenance').
'Drip tray not fitted'	The drip tray is not inserted correctly or is not inserted at all. You cannot prepare any products.	▶ Fit the drip tray.
'Fill bean container'	The bean container is empty. You cannot prepare any speciality coffees, but you can prepare hot water and milk.	▶ Fill the bean container (see Chapter 1 'Preparing and using for the first time – Filling the bean container').
'Rinse the milk system'	The E6 requests a milk system rinse.	▶ Perform milk system rinsing (see Chapter 5 'Maintenance – Rinsing the fine foam frother').
The filter symbol at the bottom of the display lights up red.	The filter cartridge no longer works.	▶ Replace the CLARIS Smart filter cartridge (see Chapter 5 'Maintenance – Inserting/ changing the filter').
'Clean machine'	The E6 is prompting you to clean it.	▶ Perform cleaning (see Chapter 5 'Maintenance – Cleaning the machine').
'Decalcify machine'	The E6 is prompting you to descale it.	▶ Perform descaling (see Chapter 5 'Maintenance – Descaling the machine').
'Too hot'	The system is too hot to start a maintenance programme.	▶ Wait for several minutes until the system has cooled or prepare a speciality coffee or hot water.

7 Troubleshooting

Problem	Cause/Result	Action
Insufficient foam is produced when the milk is frothed or milk sprays out of the fine foam frother.	The fine foam frother is dirty.	<ul style="list-style-type: none"> ▶ Clean the fine foam frother (see Chapter 5 'Maintenance – Cleaning the fine foam frother'). ▶ Dismantle and rinse the fine foam frother (see Chapter 5 'Maintenance – Dismantling and rinsing the fine foam frother').
Coffee only comes out in drips when it is being prepared.	The coffee is ground too finely and obstructs the system. The water hardness may not have been correctly set.	<ul style="list-style-type: none"> ▶ Set the grinder to a coarser setting (see Chapter 2 'Preparation – Adjusting the grinder'). ▶ Perform descaling (see Chapter 5 'Maintenance – Descaling the machine ').
There is dry ground coffee behind the coffee grounds container.	The beans used are resulting in an above-average volume of ground coffee.	▶ Reduce the coffee strength or choose a finer grinder setting (see chapter 4 'Permanent settings in programming mode – Adjusting the product settings').
'Fill water tank' is displayed although the water tank is full.	The water tank float is trapped.	▶ Descale the water tank (see Chapter 5 'Maintenance – Descaling the water tank').
Little or no water or steam comes out of the fine foam frother. The pump is very quiet.	The connector of the fine foam frother may be blocked by milk residues or limescale fragments loosened during descaling.	<ul style="list-style-type: none"> ▶ Remove the fine foam frother. ▶ Unscrew the black connector. ▶ Clean the connector thoroughly. ▶ Screw the connector back on tightly by hand.
Grinder is making a very loud noise.	There are foreign objects in the grinder.	▶ Contact customer support in your country (see Chapter 11 'JURA contact details / Legal information').

7 Troubleshooting

Problem	Cause/Result	Action
'ERROR 2' or 'ERROR 5' is displayed.	If the machine has been exposed to the cold for a long period of time, heating may be disabled for safety reasons.	► Warm the machine at room temperature.
Other 'ERROR' messages are displayed.	-	► Switch the E6 off with the On/Off button  . Contact customer support in your country (see Chapter 11 'JURA contact details / Legal information').

- i** If you were unable to solve the problem, contact customer support in your country (see Chapter 11 'JURA contact details / Legal information').

8 Transport and environmentally friendly disposal

Transport / Emptying the system




Keep the packaging for your E6. It should be used to protect the machine during transport.

In order to protect the E6 from frost during transport, the system must be emptied.

Precondition: The start screen is displayed.

- ▶ Remove the milk pipe from the fine foam frother.
- ▶ Place a receptacle under the fine foam frother.
- ▶ Press the 'Milk foam' button.

As soon as the machine has heated up, 'Open switch' appears.

- ▶ Turn the switch to the  position.
'Milk foam', hot steam is discharged from the fine foam frother.
 - ▶ Remove and empty the water tank.
 - ▶ Press the '>' button several times until 'Amount of milk' / '60 sec.' is displayed.
Steam will continue to be discharged from the fine foam frother until the system is empty.
'Close switch'
 - ▶ Turn the switch to the  position.
'Fill water tank'
 - ▶ Press the On/Off button .
- Your E6 is switched off.



Disposal

Please dispose of old machines in an environmentally neutral way.



Old machines contain valuable, recyclable materials which should be recycled. Please therefore dispose of old machines via suitable collection systems.

9 Technical data

Voltage	220 – 240 V ~, 50 Hz
Power	1450 W
Conformity mark	CE
Pump pressure	static, max. 15 bar
Holding capacity of water tank (without filter)	1.9 l
Holding capacity of bean container	280 g
Holding capacity of coffee grounds container	max. 16 portions
Cable length	approx. 1.1 m
Weight	approx. 9.6 kg
Dimensions (W × H × D)	28.0 × 35.1 × 43.9 cm

Wireless connections

CLARIS Smart filter cartridge (RFID technology)	Frequency band 13.56 MHz Max. transmission power < 1 mW
JURA Smart Connect (Bluetooth connection)	Frequency band 2.4 GHz Max. transmission power < 1 mW

Information for testers (repeat test in accordance with DIN VDE 0701-0702): The central grounding point (CGP) is located on the underside of the machine, right next to the mains cable's connection point.

10 Index

A

- Addresses 44
- Adjusting the product settings 22
- Aroma preservation cover
 - Bean container with aroma preservation cover 4
- Automatic switch-off 24

B

- Bean container
 - Bean container with aroma preservation cover 4
 - Cleaning 33
 - Filling 10
- Bluetooth 13, 38
- Bus bar
 - Technical data 38
- Button
 - On/Off button 4
- Bypass amount of water 15

C

- Caffè Barista 15
- Cappuccino 15
- Central grounding point 38
- CLARIS Smart filter cartridge
 - Changing 28
 - Inserting 28
- Cleaning
 - Bean container 33
 - Fine foam frother 27
 - Machine 29
- Coffee 14
 - Two coffees 14
- Coffee grounds container 4
- Coffee spout
 - Height-adjustable coffee spout 4
- Connect accessory 13
- Consistency of grind
 - Adjusting the grinder 18
 - Grinder adjustment switch 4
- Contact details 44
- Cover
 - Filler funnel for cleaning tablet 4
 - Water tank 4
- Cup grille 4
- Customer support 44

D

- Daily maintenance 19
- Declaration of Conformity 44
- Descaling
 - Machine 30
 - Water tank 32
- Display 5
- Display messages 34
- Disposal 37
- Double product 14
- Drip tray 4

E

- Emptying the system 37
- Errors
 - Troubleshooting 35
- Espresso 14
 - Two espressi 14
- Espresso doppio 16
- EU Declaration of Conformity 44

F

- Filler funnel
 - Filler funnel for cleaning tablet 4
- Filling
 - Bean container 10
 - Water tank 19
- Filter
 - Changing 28
 - Inserting 28
- Fine foam frother 4
 - Cleaning 27
 - Dismantling and rinsing 28
 - Rinsing 26
- First-time use 11

G

- Grinder adjustment switch 4
- Grounding point 38

H

- Height-adjustable coffee spout 4
- Hotline 44
- Hot water 17
- Hot water and steam preparation
 - Switch for hot water and steam preparation 5

J

JURA

Contact details 44

L

Language 25

M

Macchiato 15

Machine

Cleaning 29

Daily maintenance 19

Descaling 30

Regular maintenance 20

Rinsing 26

Setting up 10

Switching off 20

Switching on 19

Mains cable 4

Maintenance 26

Daily maintenance 19

Regular maintenance 20

Messages, display 34

Milk

Connecting milk 12

Milk foam 16

Milk system

Cleaning the fine foam frother 27

Rinsing the fine foam frother 26

P

Permanently setting the water for the cup size 17

Permanent settings in programming mode 22

Preparation 14

Cappuccino 15

Coffee 14

Espresso 14

Espresso doppio 16

Hot water 17

Lungo Barista 15

Macchiato 15

Milk foam 16

Two coffees 14

Two espressos 14

Two speciality coffees 14

Problems

Troubleshooting 35

Product settings

Adjusting 22

Programming mode 22

Automatic switch-off 24

Language 25

Setting the water hardness 24

Unit for amount of water 25

Proper use 6

R

Regular maintenance 20

Rinsing

Fine foam frother 26

Machine 26

S

Safety 6

Safety information 6

Settings

Permanent settings in programming mode 22

Setting up

Setting up the machine 10

Smart Connect 13

Switch for hot water and steam preparation 5

Switching off 20

Switching on 19

Switch-off

Automatic switch-off 24

Symbol description 3

T

Technical data 38

Tel 44

Transport 37

Troubleshooting 35

Two products 14

U

Unit for amount of water 25

Use, First-time 11

W

Water hardness

Determining the water hardness 10

Setting the water hardness 24

Water tank 4

Descaling 32

Filling 19

Wireless connection 9, 11, 13, 28, 38

11 JURA contact details / Legal information

JURA Elektroapparate AG
Kaffeeweltstrasse 10
CH-4626 Niederbuchsiten
Tel. +41 (0)62 38 98 233

- i** You will find additional contact details for your country at **jura.com**.
- i** If you need assistance with using your machine, you can find this at **jura.com/service**.

- Directives** The machine complies with the following directives:
- 2014/35/EU – Low Voltage Directive
 - 2014/30/EU – Electromagnetic Compatibility
 - 2009/125/EC – Ecodesign Directive
 - 2011/65/EU – RoHS Directive
 - 2014/53/EU – Wireless Voltage Directive

A detailed EU Declaration of Conformity for your E6 can be found at **jura.com/conformity**.

- Technical changes** We reserve the right to make technical changes. The diagrams used in these instructions for use are for illustration purposes only and do not represent the original colours of the machine. Some details of your E6 may vary.

- Feedback** Your opinion is important to us! Use the contact details at **jura.com**.

- Copyright** The instructions for use contain information which is protected by copyright. It is not permitted to photocopy these instructions for use or translate them into another language without the prior written consent of JURA Elektroapparate AG.